PRODUCT NAME: ADHESIVE SPRAY

PRODUCT CODE: B015390

HMIS CODES: H F R P

2 4 0 x

MANUFACTURER'S NAME: VARN PRODUCTS

ADDRESS: 905 SOUTH WESTWOOD, ADDISON, ILLINOIS 60101

EMERGENCY PHONE: (800) 424-9300 INFORMATION PHONE: (800) 336-8276

DATE REVISED: 06-19-96 NAME OF PREPARER: VARN PRODUCTS CO.

REASON REVISED : UPDATE; SUPERSEDES ALL PREVIOUS REVISIONS.

======= SECTION II - HAZARDOUS INGREDIENTS/SARA III INFORMATION ========

The second second second second

			OCCUPATIONAL EXPOSURE LIMITS VAPO					WEIGHT
HAZARDOUS COMPONENTS	+ +3**	CAS NUMBER	OSHA PEL	ACGIE TLV	OTHER	mm Eg (	TEMP P	PERCENT
LIQUIPIED PETROLEUM GAS	·	68476-85-7	1000 ppm	1000 ppm	:	760.0	602	55
•CYCLOHENANE		110-82-7	N/B	300 ppm	N/E	98.0	772	32
	The second design of the second of the secon	car of the more Chamas Bear and origin is on the con-	marine your war was referenced.	and the second s	and the second section in the second	garagas gaile		

\* Indicates toxic chemical(s) subject to the reporting requirements of section 313 of Title III and of 40 CFR 372.

ALL INGREDIENTS LISTED IN THE EPA TSCA INVENTORY. CONTAINS NO OZONE DEPLETING SUBSTANCES.

\*\* THIS PRODUCT IS CONSIDERED TO BE FLAMMABLE AS DESCRIBED IN 16CPR 1500.45.

======== SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT: N/A SPECIFIC GRAVITY (H2O=1): 0.6

VAPOR DENSITY: HEAVIER THAN AIR EVAPORATION RATE: FASTER THAN ETHER

MATERIAL V.O.C.: 4.41 LB/GL ( 528 G/L)

SOLUBILITY IN WATER: NEGLIGIBLE VAPOR PRESSURE: 65 psig @130 Deg F

APPEARANCE AND ODOR: AEROSOL CAN; LIGHT TAN SPRAY - MILD ODOR

FLASH POINT: SEE \*\* METHOD USED: SECTION II

FLAMMABLE LIMITS IN AIR BY VOLUME- LOWER: 1.8% UPPER: 9.2

EXTINGUISHING MEDIA: FOAM, CO2, DRY CHEMICAL

#### SPECIAL FIREFIGHTING PROCEDURES

KEEP CONTAINERS COOL. USE SHIELDING TO PROTECT PERSONNEL AGAINST BURSTING, RUPTURING OR VENTING CONTAINERS. WATER MAY NOT BE EFFECTIVE TO EXTINGUISH FIRE. USE WATER SPRAY TO COOL FIRE EXPOSED CONTAINERS.

## UNUSUAL FIRE AND EXPLOSION HAZARDS

AT ELEVATED TEMPERATURES (OVER 130 Deg F) CONTAINERS MAY VENT, RUPTURE OR BURST.

EXECUTED TO THE REAL PROPERTY OF THE PROPERTY

STABILITY: STABLE CONDITIONS TO AVOID AVOID EXCESS HEAT (ABOVE 130 Deg F).

INCOMPATIBILITY (MATERIALS TO AVOID)

AVOID MIXING WITH STRONG OXIDIZING MATERIALS.

HAZARDOUS DECOMPOSITION OR BYPRODUCTS

BURNING WILL PRODUCE OXIDES OF CARBON. ADDITIONAL TOXIC CHEMICALS MAY BE FORMED IN SMALL AMOUNTS.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR

INHALATION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

EXCESSIVE VAPOR CONCENTRATIONS ARE ATTAINABLE. OVEREXPOSURE MAY IRRITATE THE MOSE, THROAT, LUNGS AND CAUSE CENTRAL MERVOUS SYSTEM DEPRESSION WITH SYMPTOMS SUCH AS DROWSINESS, DIZZINESS AND UNCONSCIOUSNESS.

SKIN AND EYE CONTACT HEALTH RISKS AND SYMPTOMS OF EXPOSURE

SKIN AND EYE CONTACT MAY PRODUCE MODERATE IRRITATION.

SKIN ABSORPTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

A SINGLE, PROLONGED EXPOSURE IS NOT LIKELY TO RESULT IN THE MATERIAL BEING ABSORBED THROUGH THE SKIN IN HARMFUL AMOUNTS.

INGESTION HEALTH RISKS AND SYMPTOMS OF EXPOSURE

INGESTION MAY PRODUCE GASTRO-INTESTINAL IRRITATION, VOMITING AND POSSIBLE DAMAGE TO VITAL ORGANS. FOLLOW FIRST AID PROCEDURES.

HEALTH HAZARDS (ACUTE AND CHRONIC)

REPEATED AND ABUSIVE BREATHING OF CONCENTRATED VAPORS MAY EFFECT PULMONARY, CARDIOVASCULAR, CENTRAL NERVOUS SYSTEM AND CAUSE LIVER, LUNG AND KIDNEY EFFECTS. REPEATED SKIN CONTACT WILL DRY OUT AND CRACK SKIN.

CARCINOGENICITY: NTP? NO IARC MONOGRAPHS? NO OSHA REGULATED? NO THIS PRODUCT CONTAINS NO KNOWN CARCINOGENS.

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE

SKIN CONTACT MAY AGGRAVATE PRE-EXISTING DERMATITIE. INHALATION MAY AGGRAVATE PRE-EXISTING ASTHMA-LIKE CONDITIONS.

EMERGENCY AND FIRST AID PROCEDURES

EYES: HOLD BYELID OPEN AND FLUSH WITH WATER FOR 15 MINUTES. CONTACT A PHYSICIAN IF IRRITATION PERSISTS.

SKIN: WASH WITH SOAP AND WATER.

INGESTION: CONTACT LOCAL POISON CONTROL CENTER OR PHYSICIAN IMMEDIATELY.

INHALATION: MOVE TO FRESH AIR. GIVE OXYGEN IF BREATHING IS LABORED.

## PAGE 3 OF 3

#### B015390

#### MATERIAL SAFETY DATA SHEET

======== SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE ==========

#### STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED

ELIMINATE ALL IGNITION SOURCES. SOAK UP MATERIAL WITH ABSORBANT. TRANSFER INTO A CLOSED CONTAINER FOR LATER DISPOSAL. AEROSOL PROPELLENTS ARE EXTREMELY FLAMMABLE.

## WASTE DISPOSAL METHOD

DO NOT PUNCTURE OR INCINERATE. DISPOSE OF AS HAZARDOUS WASTE IN ACCORDANCE WITH EPA RCRA. CONTACT A LICENSED HAZARDOUS WASTE HAULER FOR MORE INFORMATION.

# PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING

KEEP AWAY FROM SUNLIGHT, EXCESS HEAT, SPARKS, FLAMES AND OTHER SOURCES OF IGNITION. STORE AT TEMPERATURE BELOW
130 Deg F. AVOID SKIN CONTACT. AVOID BREATHING VAPORS. WEAR PROPER PERSONAL PROTECTIVE EQUIPMENT WHEN USING THIS
PRODUCT. STORE AS A LEVEL 3 AEROSOL (NFPA 30B).

#### OTHER PRECAUTIONS

FOR AIR SHIPMENT: DOT PROPER SHIPPING NAME: AEROSOLS, HAZARD CLASS: 2.1, UN NUMBER: UN1950, PACKING GROUP: N/A
FOR SURFACE SHIPMENT: DOT PROPER SHIPPING NAME: CONSUMER COMMODITY, HAZARD CLASS: ORM-D, UN NUMBER: NONE,
PACKING GROUP: N/A

# RESPIRATORY PROTECTION

WHEN CONCENTRATIONS EXCEED THE ESTABLISHED EXPOSURE LIMITS IN SECTION II, USE A RESPIRATOR WITH APPROPRIATE ORGANIC VAPOR CARTRIDGES (NIOSH APPROVED).

## **VENTILATION**

IF CURRENT VENTILATION IS INADEQUATE TO MAINTAIN CONCENTRATIONS BELOW THE ESTABLISHED EXPOSURE LIMITS IN SECTION II, ADDITIONAL VENTILATION OR EXHAUST SYSTEMS IS REQUIRED. EXPLOSION PROOF ELECTRICAL SYSTEMS MUST BE USED.

#### PROTECTIVE GLOVES

POR BRIEF CONTACT, NO PRECAUTIONS SHOULD BE NEEDED.

### EYE PROTECTION

WEAR SAPETY GLASSES WITH SIDE SHIELDS.

## OTHER PROTECTIVE CLOTHING OR EQUIPMENT

A PERSONAL PROTECTIVE RATING OF X MEANS YOU MUST SEE YOUR SUPERVISOR FOR GUIDANCE. OSHA REGULATIONS (29CFR PART 1910, SUBPART 1) REQUIRE EMPLOYERS TO EVALUATE PERSONAL PROTECTIVE EQUIPMENT REQUIRMENTS IN THE MORKPLACE.

### WORK/HYGIENIC PRACTICES

WASH WITH SOAP AND WATER AFTER PRODUCT CONTACT WITH SKIN.

#### DISCLAIMER

THE INFORMATION ON THIS MSDS IS BELIEVED TO BE ACCURATE AS OF THE DATE SHOWN IN SECTION I. SINCE THE USE OF THIS PRODUCT IS NOT UNDER THE CONTROL OF VARM, IT IS THE USER'S RESPONSIBILITY TO DETERMINE WHAT CONSTITUTES SAPE USAGE FOR A PARTICULAR PRODUCT. THIS FORM MAY BE REPRODUCED IN QUANTITIES NECESSARY TO MEET YOUR REQUIREMENTS.